FACILITY INFORMATION						
FACILITY NAME: ALOHA PETE	ROLEUM KAHUL	UI TERMINAL	ter a state	า สาระกับอะ	an na y Nili nan	non tenine petroni retrike metroni
LATITUDE: 20.89334		LONGITUDE: 18	Section/Township/Range: Sectio			ange: amasp & u uon an
FRS#:	OIL DATAB	IL DATABASE ID NO:			ICIS#:	se to a conflictor of the
ADDRESS: 60 HOBRON AVE	and the left to	yaan saa saa aa a	- perturi	Saltange 11		e setemat en mesen mon [1]
CITY: KAHULUI	makining ST	ATE: HI	ZIP:	96732	i dil " ne	COUNTY: MAUI
MAILING ADDRESS (IF DIFFER	RENT FROM F					
CITY:	ST	ATE:	ZIP:			COUNTY: Authorities
TELEPHONE:	•	FACILITY REPRI	ESENTATI	VE NAME:	Joseph Lo	van, Terminal Manager
OWNER NAME: Aloha Petroleur	m Ltd.					
OWNER ADDRESS: 1132 Bisho	p Street, Suite	700				
CITY: Honolulu	ST	ATE: HI	ZIP:	96813		COUNTY: Honolulu
OWNER CONTACT PERSON:	Wayne Condit -	General Manager, Te	rminals and	Transportati	on	
						wcondit@alohagas.com
FACILITY OPERATOR NAME (I	F DIFFERENT	FROM OWNER -	IF NOT, P	RINT "SAM	IE"): "SAM	Control of the action of the Edward Control of the
OPERATOR ADDRESS:	photographic and	maligright trighting Isw old piven offs	Source Link	In grade (and red talls at all species	per ne vicenname l'h ee extent
CITY:	ST	ATE:	ZIP:			COUNTY:
TELEPHONE:		OPERATOR CO	NTACT PE	RSON:		
FACILITY TYPE: Petroleum Bulk	Stations and Te	rminals				NAICS CODE: 424710
HOURS PER DAY FACILITY AT	TENDED: M-	F, 0700 - 1700	TOTA	L FACILIT	Y CAPACI	ΓY: >1,000,000 gallons
TYPE(S) OF OIL STORED: Train	nsmix, additives	diesel, oily wastewat	er	man en X	li Ewy III.	Baran i iya şiyen ilk şe kayınının sen
LOCATED IN INDIAN COUNTR	Y? YES	NO RESERVAT	ION NAME	Malaalii Waxaa aa		ntices and a tradest taken op ne en ein. Tradest portunes (1 in 1655) en
INSPECTION INFORMATION	N		- oaksa	Afrika un loca	incod Su	in vision agreem teats which personner :
INSPECTION DATE: 18 July 201	3 2 2 - 1 - 2 - 2 1 - 1 - 1 - 1 - 1 - 1 - 1	TIME: 0845	A	CTIVITY IE	NO: 13-4	041 a 150 dan 5, 165, 167 a 1 , 1676 gira ()
LEAD INSPECTOR: Janice Witul	destroy to and	- Table War sales	12.73	OF 164, 20	Or sum.	Shore had applied be hitten as all to
OTHER INSPECTOR(S): N/A	ethica manasiqui anni	se menahuppe se menahuppe				e en a company of the
INSPECTOR ACKNOWLED	GMENT					THE MODEL TO GET VANDA
I performed an SPCC inspection	at the facility :	specified above.				gy stretchen is which is recognized to the majority of a
INSPECTOR SIGNATURE:	the)		(8)97(1		((5)-09)	DATE: 9/18/2013

FACILITY RESPONSE PLAN (FRP) APPLICABILITY	100	
A non-transportation related onshore facility is required to prepare and impler The facility transfers oil over water to or from vessels and has a tota 42,000 U.S. gallons, OR The facility has a total oil storage capacity of at least 1 million U.S. g The facility does not have secondary containment sufficiently la tank plus sufficient freeboard for precipitation. The facility is located at a distance such that a discharge could environments. The facility is located such that a discharge would shut down a The facility has had a reportable discharge greater than or equal	I oil storage capacity greater than allons, AND at least one of the fol rge to contain the capacity of the l cause injury to fish and wildlife an public drinking water intake.	or equal to lowing is true: argest aboveground d sensitive
Facility has FRP: Yes No Not Required 10,244 1014 11 223440	FRP Number: FRP - 09-0034	FULL MAS AUTORER SEE UP
Facility has a completed and signed copy of Appendix C, Attachment C-II, "Certification of the Applicability of the Substantial Harm Criteria."		✓Yes No
Comments: YTMUOD 915	SIAIE	- 41
SPCC GENERAL APPLICABILITY—40 CFR 112.1	and I	1374 (1.1.24 A)
IS THE FACILITY REGULATED UNDER 40 CFR part 112?		
oil storage capacity is over 1,320 U.S. gallons AND The facility is a non-transportation-related facility engaged in drilling, pro- processing, refining, transferring, distributing, using, or consuming oil and location could reasonably be expected to discharge oil into or upon the n States	d oil products, which due to its	✓Yes No
AFFECTED WATERWAY(S): Kahului Bay	DISTANCE: 0.25 miles	1714
FLOW PATH TO WATERWAY: Overland and storm drains	PARAGE STREET	Janga Baging - Jima - Firsa - Jima - Jima
Transportation, U.S. Department of the Interior, or Minerals Management Service, as defined in Memoranda of Understanding dated November 24, 1971, and November 8, 1993; Tank trucks that return to an otherwise regulated facility that contain only residual amounts of oil (EPA Policy letter) Completely buried tanks subject to all the technical requirements of 40 CFR part 280 or a state program approved under 40 CFR part 281; Underground oil storage tanks deferred under 40 CFR part 280 that supply emergency diesel generators at a nuclear power generation facility licensed by the Nuclear Regulatory Commission (NRC) and subject to any NRC provision regarding design and quality criteria, including but not limited to CFR part 50; Any facility or part thereof used exclusively for wastewater treatment (production recovery or recycling of oil is not considered wastewater.)	PCC requirements: ontainers smaller than 55 U.S. gallons ermanently closed containers (as defined in § ot-mix asphalt or any hot-mix asphalt or eating oil containers used solely at a sesticide application equipment and reformit and milk product container and opurtenances; and tra-facility gathering lines subject to the 49 CFR part 192 or 195.	ned in §112.2); (112.2); (containers; (ingle-family residence; (ated mix containers; (d associated piping and (e regulatory requirements
Does the facility have an SPCC Plan?	✓Yes No	

SPCC TIER II	QUALIFIED FA	CILITY APPLICABILIT	Y-40 CFR 112.3(g)(2)	n saler ve na etk	
In the three year	rs prior to the SPC	torage capacity is 10,000 local corage capacity is 10,000 local corage. CP lan self-certification dess than three years), the	ate, or since becoming sul	oject to the rule (if the	∏Yes ✓No
		ed in §112.1(b) exceeding			✓Yes □No
 Two discharge period¹ 	ges as described	n §112.1(b) each exceedi	ng 42 U.S. gallons within a	any twelve-month	✓Yes No
			FACILITY IS CONSIDERE		
REQUIREMEN	ITS FOR PREP	ARATION AND IMPLE	MENTATION OF A SP	CC PLAN—40 CFR 1	12.3
Date facility beg	an operations: SI	HELL until November 2010	ent at teathwither a sec a	er uni ya nshipet aspar	THE SAME I TRANSPORTED
Date of initial SP	PCC Plan prepara	tion: UNKNOWN	Current Plan version (dat	te/number): June 2012	
112.3(a)	In operation implemente Beginning of	on or prior to November d by November 10, 2011	nobile or portable faciliti 10, 2011: Plan prepared a r 10, 2011, Plan prepared	ind/or amended and fully	Yes No NA
	For farms (as d In operation implemente Beginning of fully implementer	efined in §112.2): n on or prior to August 16, and by May 10, 2013 experations after August 16 ented by May 10, 2013 experations after May 10, 2	2002: Plan maintained, ar , 2002 through May 10, 20 013: Plan prepared and fu	013: Plan prepared and	Yes No ✓NA Yes No ✓NA Yes No ✓NA
112.3(d)	PE attests: PE is famili PE or agen Plan is prep of applicabl Procedures	ar with the requirements of the has visited and examine pared in accordance with good industry standards and	The Control of the Co	including consideration R part 112	Yes No NA
PE Name: VICT	OR DUSPIVA	License No.: 15235-C	State: HI	Date of certification	on: 2/28/13*
112.3(e)(1)	available at the	nearest field office.	st 4 hours per day. If facili		Yes No NA
PLA	NTAINMENT FLOOI	R. NO INDICATION IN PLAI BASED ON MANWAYS OF	OF IMPERMEABILITY REQ N ON DURING INSPECTION CLOSED TANKS REMAININ	THAT ANY ACTION HAD I	12 CONCERNING BEEN TAKEN.

¹ Oil discharges that result from natural disasters, acts of war, or terrorism are not included in this determination. The gallon amount(s) specified (either 1,000 or 42) refers to the amount of oil that actually reaches navigable waters or adjoining shorelines not the total amount of oil spilled. The entire volume of the discharge is oil for this determination.

² An owner/operator who self-certifies a Tier II SPCC Plan may not include any environmentally equivalent alternatives or secondary containment impracticability determinations unless reviewed and certified by a PE.

AMENDMENT	OF SPCC PLA	N BY REGIONAL ADM	INISTRATOR (RA)—40 CFR 112.4	HEADERSTON
112.4(a),(c)	Has the facility of discharge or mo month period? ³ Was inform Was inform pollution co Date(s) and	ischarged more than 1,000 re than 42 U.S. gallons in e	O U.S. gallons of oil in each of two reportables as required in §112.4 ropriate agency or agin which the facility ischarges(s) under the IRC ⁵ ?	n a single reportable le discharges in any 12- l4(a)? ⁴ gencies in charge of oil s located§112.4(c) nis section:	Yes No No NA Yes No NA Yes No NA
		त्रस्य १ होता दः(६) फल्प स्व	118, 4, 1 of <u>A</u> 91 3 W	ran wasawa - p. K. Pal	
AMENDMENT	OF SPCC PLA	N BY THE OWNER OR	OPERATOR-40	CFR 112.5	
112.5(a)	Has there been a change at the facility that materially affects the potential for a discharge described in §112.1(b)?				☐Yes ☑No
If YES	Was the Plan	an amended within six mor	nths of the change?	ant of a state of the land to another control of May 10, 20	Yes No
112.5(b)	Review and evaluation of the Plan completed at least once every 5 years? Following Plan review, was Plan amended within six months to include more effective prevention and control technology that has been field-proven to significantly reduce the likelihood of a discharge described in §112.1(b)? Amendments implemented within six months of any Plan amendment? Five year Plan review and evaluation documented?				
112.5(c)	Professional Engapplicable requir	ineer certification of any te ements of §112.3(d) [Exce	echnical Plan amend	ments in accordance with all	Yes No NA
Name:		License No.:	State:	Date of certificatio	n:
	ithin six months o	f the change? six months of any Plan am	endment?		☐Yes ☐No ☑NA ☐Yes ☐No ☑NA
Comments: 112.	5(b),(c) - ADDRESS	SED IN PLAN			8 7

⁵ Inspector Note-Confirm any spills identified above were reported to NRC

³ A reportable discharge is a discharge as described in §112.1(b)(see 40 CFR part 110). The gallon amount(s) specified (either 1,000 or 42) refers to the amount of oil that actually reaches navigable waters or adjoining shorelines not the total amount of oil spilled. The entire volume of the discharge is oil for this determination.

⁴ Triggering this threshold may disqualify the facility from meeting the Qualified Facility criteria if it occurred in the three years prior to self certification.

112.6(b)(1)	Plan Certification: Owner/operator certified in the Plan that:	Yes No No
	He or she is familiar with the requirements of 40 CFR part 112	Yes No No
	He or she has visited and examined the facility ⁶	
	The Plan has been prepared in accordance with accepted and sound industry practices and standards and with the requirements of this part	Yes No VN
(iv)	Procedures for required inspections and testing have been established	Yes No No
(v)	He or she will fully implement the Plan	Yes No No
(vi)	The facility meets the qualification criteria set forth under §112.3(g)(2)	Yes No No
7.15	The Plan does not deviate from any requirements as allowed by §§112.7(a)(2) and 112.7(d), except as described under §112.6(b)(3)(i) or (ii)	Yes No No
(viii)	The Plan and individual(s) responsible for implementing the Plan have the full approval of management and the facility owner or operator has committed the necessary resources to fully implement the Plan.	Yes No VN
112.6(b)(2)	Technical Amendments: The owner/operator self-certified the Plan's technical amendments for a change in facility design, construction, operation, or maintenance that affected potential for a §112.1(b) discharge	Yes No No
If YES	 Certification of technical amendments is in accordance with the self-certification of provisions of §112.6(b)(1). 	□Yes □No ☑N
(i)	A PE certified a portion of the Plan (i.e., Plan is informally referred to as a hybrid Plan)	Yes No VN
If YES	 The PE also certified technical amendments that affect the PE certified portion of the Plan as required under §112.6(b)(4)(ii) 	☐Yes ☐No ☑N
(ii)	The aggregate aboveground oil storage capacity increased to more than 10,000 U.S. gallons as a result of the change	☐Yes ☐No ☑N
If YES	The facility no longer meets the Tier II qualifying criteria in §112.3(g)(2) beca it exceeds 10,000 U.S. gallons in aggregate aboveground storage capaci	ause ty.
	The owner/operator prepared and implemented a Plan within 6 months following the change and had it certified by a PE under §112.3(d)	Yes No 7
112.6(b)(3)	Plan Deviations: Does the Plan include environmentally equivalent alternative methods or impracticability determinations for secondary containment?	☐Yes ☐No ☑N
If YES	Identify the alternatives in the hybrid Plan:	6.
	 Environmental equivalent alternative method(s) allowed under §112.7(a)(2); 	Yes No V
	Impracticability determination under §112.7(d) against a fine pulhorar search guidest a fine pulhorar search guidest.	Yes No I
112.6(b)(4)	For each environmentally equivalent measure, the Plan is accompanied by a written statement by the PE that describes: the reason for nonconformance, the alternative measure, and how it offers equivalent environmental protection in accordance with	Yes No V
J: 11	measure, and how it offers equivalent environmental protection in accordance with serior \$112.7(a)(2);	e to 1 pp legga
	 For each secondary containment impracticability determination, the Plan explains the reason for the impracticability determination and provides the alternative measures to secondary containment required in §112.7(d) 	Yes No 7
10-2_1	AND and and equiposal equiposal equiposal exercises and equiposal	duard
(i)	PE certifies in the Plan that: (3.05 ,3.9f3/1911 (Blast bits ,phibsolinu ,phibsol) shuborq to pri	Lance I was a second
(A)	He/she is familiar with the requirements of 40 CFR Part 112	Yes No /
(B)	He/she or a representative agent has visited and examined the facility	Yes No I
(C)	The alternative method of environmental equivalence in accordance with §112.7(a)(2) or the determination of impracticability and alternative measures in accordance with §112.7(d) is consistent with good engineering practice, including consideration of applicable industry standards, and with the requirements of 40 CFR Part 112.	Yes No 7
mments:	this periode in a period of a first term, was a supplication [Tyes T Ma	

⁶ Note that only the person certifying the Plan can make the site visit and additional particular and another than the person certifying the Plan can make the site visit.

GENERAL SP	PCC REQUIREMENTS—40 CFR 112.7	PLAN	FIELD
Management ap fully implement	proval at a level of authority to commit the necessary resources to the Plan ⁷	Yes No. 13 Salvas	
Plan follows sec requirements an	uence of the rule or is an equivalent Plan meeting all applicable rule d includes a cross-reference of provisions	Yes No NA	
details of their in	acilities, procedures, methods, or equipment not yet fully operational, installation and start-up are discussed (Note: Relevant for inspection esting baselines.)	Yes No NA	
112.7(a)(2)	The Plan includes deviations from the requirements of §§112.7(g), (h)(2) and (3), and (i) and applicable subparts B and C of the rule, except the secondary containment requirements in §§112.7(c) and (h)(1), 112.8(c)(2),112.8(c)(11), 112.12(c)(2), and 112.12(c)(11) The Plan states reasons for nonconformance	☐Yes ☑No ☐NA ☐Yes ☑No ☐NA	
ALC: LPC	Alternative measures described in detail and provide equivalent environmental protection (Note: Inspector should document if the environmental equivalence is implemented in the field, in accordance with the Plan's description)	☐Yes ☑No ☐NA	Yes No NA
Describe each d	eviation and reasons for nonconformance:	s le il di altin nerlealitin respense estata mantan	icay is
	so states that the secondary containment area will be lined, although no schedu	n Pf. slov varibes lath in Skarequally made 5	PH STATE OF THE ST
112.7(a)(3)	Plan describes physical layout of facility and includes a diagram ⁸	✓Yes No	✓Yes □No
AND - AD - MB - MD - MB - LD	that identifies: Location and contents of all regulated fixed oil storage containers Storage areas where mobile or portable containers are located Completely buried tanks otherwise exempt from the SPCC requirements (marked as "exempt") Transfer stations Connecting pipes, including intra-facility gathering lines that are otherwise exempt from the requirements of this part under §112.1(d)(11)	100000000000000000000000000000000000000	Pegna Russel (857 ff
And I had be	Plan addresses each of the following:	reach endron hendla tement ov the PL trate	of e (a ((a)a.e.c.)
(i)	For each fixed container, type of oil and storage capacity (see Appendix A of this checklist). For mobile or portable containers, type of oil and storage capacity for each container or an estimate of the potential number of mobile or portable containers, the types of oil, and anticipated storage capacities	Yes Non Street 12 7:21(2)(2) 12 7:21(2)(2) 12 7:21(2) 12 7:21(2) 12 7:21(2) 12 7:21(2) 12 7:21(2)(2)(2)(2)(2)(2)(2)(2)(2)(2)(2)(2)(2)(1
(ii)	Discharge prevention measures, including procedures for routine handling of products (loading, unloading, and facility transfers, etc.)	☑Yes ☐No	☑Yes ☐No
	Discharge or drainage controls, such as secondary containment around containers, and other structures, equipment, and procedures for the control of a discharge	✓Yes No	✓Yes □No
(iv)	Countermeasures for discharge discovery, response, and cleanup (both facility's and contractor's resources)	☑Yes ☐No	☑Yes □No
(v)	Methods of disposal of recovered materials in accordance with applicable legal requirements	☑Yes ☐No	
(vi)	Contact list and phone numbers for the facility response coordinator, National Response Center, cleanup contractors with an agreement for response, and all Federal, State, and local agencies who must be contacted in the case of a discharge as described in §112.1(b)	☑Yes □No	

May be part of the Plan or demonstrated elsewhere.
 Note in comments any discrepancies between the facility diagram, the description of the physical layout of facility, and what is observed in the field

of material discharged; attes of the total quantity discharged; attes of the quantity discharged as • Whether an evacuat	ected media; rge; caused by the discharge; to stop, remove, and of the discharge; tion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA	a discharge as
scharge as described in §112.1(b) to relate information on the: address or location and phone or of the facility; and time of the discharge; of material discharged; attes of the total quantity discharged; attes of the quantity discharged as bed in §112.1(b); or of the discharge; an apply if the facility has submitted a FRP under §112.20: anized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency under a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major and tailure where experience indicates a reasonable potential of in §112.1(b), except as provided in §112.7(k) of this sectent. The entire containment system, including walls and floors.	ected media; rge; caused by the discharge; to stop, remove, and of the discharge; tion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA	a discharge as
er of the facility; and time of the discharge; of material discharged; ates of the total quantity discharged; ates of the quantity discharged as bed in §112.1(b); at of the discharge; and the facility has submitted a FRP under §112.20: anized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency under a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major ant failure where experience indicates a reasonable potential of the state of the direction are reasonable potential of the state of the direction are reasonable potential of the direction of the direction are reasonable potential of the	rge; caused by the discharge; to stop, remove, and of the discharge; tion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
ond time of the discharge; of material discharged; ottes of the total quantity discharged; ottes of the total quantity discharged; ottes of the quantity discharged as obed in §112.1(b); of the discharge; of the	caused by the discharge; to stop, remove, and of the discharge; tion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
of material discharged; attes of the total quantity discharged; attes of the quantity discharged as bed in §112.1(b); and the discharge; Whether an evacuate have also been contain an incident facility has submitted a FRP under §112.20: analized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency under a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major and the failure where experience indicates a reasonable potential of the direction are transplanted in §112.1(b), except as provided in §112.7(k) of this section. The entire containment system, including walls and floors.	to stop, remove, and of the discharge; tion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
whether an evacuate the discharge; apply if the facility has submitted a FRP under §112.20: anized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency under a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major and failure where experience indicates a reasonable potential ment failure ate containment and/or diversionary structures or equipment din §112.1(b), except as provided in §112.7(k) of this sectent. The entire containment system, including walls and floors.	ion may be needed; and s and/or organizations who tacted. Yes No NA Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
have also been contained a submitted a FRP under §112.20: anized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency under a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major and failure where experience indicates a reasonable potential ment failure ate containment and/or diversionary structures or equipment din §112.1(b), except as provided in §112.7(k) of this section. The entire containment system, including walls and floors.	Yes No NA Yes No NA Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
anized so that portions describing procedures to be used discharge occurs will be readily usable in an emergency udes a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major ant failure where experience indicates a reasonable potential ment failure ate containment and/or diversionary structures or equipment d in §112.1(b), except as provided in §112.7(k) of this sector. The entire containment system, including walls and floors	Yes No NA are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
discharge occurs will be readily usable in an emergency udes a prediction of the direction, rate of flow, and total of oil that could be discharged for each type of major ant failure where experience indicates a reasonable potential ment failure at containment and/or diversionary structures or equipment d in §112.1(b), except as provided in §112.7(k) of this sector. The entire containment system, including walls and floors	are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
of oil that could be discharged for each type of major and failure where experience indicates a reasonable potential ament failure ate containment and/or diversionary structures or equipment d in §112.1(b), except as provided in §112.7(k) of this secent. The entire containment system, including walls and floors	are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
ant failure where experience indicates a reasonable potential oment failure ate containment and/or diversionary structures or equipment d in §112.1(b), except as provided in §112.7(k) of this secent. The entire containment system, including walls and floors	are provided to prevent tion for certain qualifies, are capable of contain	a discharge as
ate containment and/or diversionary structures or equipment d in §112.1(b), except as provided in §112.7(k) of this secent. The entire containment system, including walls and floors	tion for certain qualifie s, are capable of contain	a discharge as
d in §112.1(b), except as provided in §112.7(k) of this sec- ent. The entire containment system, including walls and floors	tion for certain qualifie s, are capable of contain	a discharge as
and capacity for secondary containment address the typical failed be discharged. See Appendix A of this checklist.	ystem before cleanup oc ailure mode and the mos	ning oil and are ccurs. The method.
hore facilities, one of the following or its equivalent: Dikes, berms, or retaining walls sufficiently • Weirs, boo	oms or other barriers;	nggy i Ngupa
Curbing or drip pensy		Sanggo Sannity
Retention	Albert Market Community of the Community	Co. Physica
Culverting, gutters or other drainage systems;	aut Anticar or streden not	40001
		diversionary
k storage containers	☑Yes ☐No ☐NA	☐Yes ☑No ☐NA
bile/portable containers	☑Yes ☐No ☐NA	☑Yes ☐No ☐NA
filled operational equipment (as defined in 112.2)	☐Yes ☐No ☑NA	☐Yes ☐No ☑NA
ner oil-filled equipment (i.e., manufacturing equipment)	☐Yes ☐No ☑NA	Yes No NA
ing and related appurtenances	✓Yes □No □NA	☑Yes ☐No ☐NA
bile refuelers or non-transportation-related tank cars	☐Yes ☐No ☑NA	☐Yes ☐No ☑NA
nsfer areas, equipment and activities	☑Yes ☐No ☐NA	☑Yes ☐No ☐NA
	✓Yes □No □NA	☑Yes ☐No ☐NA
	hore facilities, one of the following or its equivalent: Dikes, berms, or retaining walls sufficiently impervious to contain oil; Curbing or drip pans; Sumps and collection systems; Culverting, gutters or other drainage systems; which of the following are present at the facility and if approp	Thore facilities, one of the following or its equivalent: Dikes, berms, or retaining walls sufficiently weirs, booms or other barriers; impervious to contain oil; Curbing or drip pans; Sumps and collection systems; Culverting, gutters or other drainage systems; Which of the following are present at the facility and if appropriate containment and/or is or equipment are provided as described above: Ikk storage containers Which of the following are present at the facility and if appropriate containment and/or is or equipment are provided as described above: Ikk storage containers Who NA Spille diversion pond; Retention ponds; or Sorbent materials. Where facility and if appropriate containment and/or is or equipment are provided as described above: Which of the following are present at the facility and if appropriate containment and/or is or equipment are provided as described above: Which of the following are present at the facility and if appropriate containment and/or is or equipment are provided as described above: Which of the following are present at the facility and if appropriate containment and/or is or equipment and activities above: Which of the following are present at the facility and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activities above: Where facility and it is present at the facility and if appropriate containment and/or is or equipment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activities above: Where facility and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or equipment and activity and if appropriate containment and/or is or

		PLAN	FIELD
112.7(d)	Secondary containment for one (or more) of the following provisions is determined to be impracticable:	☐Yes ☑No	
	General secondary containment §112.7(c) Bulk storage containers §\$112.8(c)(2)/112.12(c)(2)	telijās utminimu ar. ģlas uspecer iestabil	
	Loading/unloading rack Mobile/portable containers§§112.7(h)(1) Containers§§112.8(c)(11)/112.1	en nelli sili meesiine ta giline siirile tadi senorio mit ir sirili kie s	
If YES	The impracticability of secondary containment is clearly demonstrated and described in the Plan	Yes No NA	☐Yes ☐No ☑NA
	 For bulk storage containers,⁹ periodic integrity testing of containers and integrity and leak testing of the associated valves and piping is conducted 	☐Yes ☐No ☑NA	☐Yes ☐No ☑NA
	(Does not apply if the facility has submitted a FRP under §112.20):	ar sopile it the racidity is	
	 Contingency Plan following the provisions of 40 CFR part 109 is provided (see Appendix C of this checklist) <u>AND</u> 	☐Yes ☐No ☑NA	
	 Written commitment of manpower, equipment, and materials required to expeditiously control and remove any quantity of oil discharged that may be harmful 	☐Yes ☐No ☑NA	Yes No NA
112.7(e)	Inspections and tests conducted in accordance with written	☑Yes ☐No	☑Yes ☐No
Innoth	Record of inspections or tests signed by supervisor or inspector	☑Yes ☐No	☑Yes □No
nd are	Kept with Plan for at least 3 years (see Appendix B of this checklist) ¹⁰	☑Yes □No	☑Yes ☐No
112.7(f)	Personnel, training, and oil discharge prevention procedures	and capacity for secon	design
(1)	Training of oil-handling personnel in operation and maintenance of equipment to prevent discharges; discharge procedure protocols; applicable pollution control laws, rules, and regulations; general facility operations; and contents of SPCC Plan	Yes No NA	☑Yes ☐No ☐NA
(2)	Person designated as accountable for discharge prevention at the facility and reports to facility management	☑Yes ☐No ☐NA	☑Yes ☐No ☐NA
(3)	Discharge prevention briefings conducted at least once a year for oil handling personnel to assure adequate understanding of the Plan. Briefings highlight and describe known discharges as described in	☑Yes ☐No ☐NA	☑Yes ☐No ☐NA
	§112.1(b) or failures, malfunctioning components, and any recently developed precautionary measures	tell diploge container	
112.7(g)	Plan describes how to: • Secure and control access to the oil handling, processing and	☑Yes ☐No ☐NA	✓ Yes ☐ No ☐ NA
ART VIET	storage areas; Secure master flow and drain valves;	America s Capitales acres	
AND AND	 Prevent unauthorized access to starter controls on oil pumps; 	Appelle (eller nore till (f	
AND SHIP	Secure out-of-service and loading/unloading connections of oil pipelines; and	wan ii kali ii saadi	
	 Address the appropriateness of security lighting to both prevent acts of vandalism and assist in the discovery of oil discharges. 	ingeger kamen dapan	TO!
Comments: Year	ly training with SPCCspill response - April 16, 2013	व्यक्तिक प्राप्त प्राप्त प्राप्त स	
10/2	5/2012 for HazWop d transport spill prevention 5/12/13		i de la disease
Road	Transport Spill prevenuon 5/12/15		- mary 81.75 ₃₁ - 216
Load	rack temp probes 5/7/13		
	level alarms		
			6
*			

⁹ These additional requirements apply only to bulk storage containers, when an impracticability determination has been made by the PE ¹⁰ Records of inspections and tests kept under usual and customary business practices will suffice

	9439 (1900)	PLAN	FIELD
112.7(h)	Tank car and tank truck loading/unloading rack ¹¹ is present at the facil		✓ Yes No
	Loading/unloading rack means a fixed structure (such as a platform, gangway) tank car, which is located at a facility subject to the requirements of this part. A unloading arm, and may include any combination of the following: piping assensers, or personnel safety devices.	loading/unloading rack in nblages, valves, pumps, s	cludes a loading or hut-off devices, overfill
If YES (1)	Does loading/unloading rack drainage flow to catchment basin or treatment facility designed to handle discharges or use a quick drainage system?	✓Yes □No□NA	Yes No NA
The Ele	Containment system holds at least the maximum capacity of the largest single compartment of a tank car/truck loaded/unloaded at the facility	☑Yes ☐No ☐NA	Yes No NA
(2)	An interlocked warning light or physical barriers, warning signs, wheel chocks, or vehicle brake interlock system in the area adjacent to the loading or unloading rack to prevent vehicles from departing before complete disconnection of flexible or fixed oil transfer lines	Yes No NA	Yes No NA
(3)	Lower-most drains and all outlets on tank cars/trucks inspected prior to filling/departure, and, if necessary ensure that they are tightened, adjusted, or replaced to prevent liquid discharge while in transit	Yes No NA	☑Yes ☐No ☐NA
112.7(i)	Brittle fracture evaluation of field-constructed aboveground containers is conducted after tank repair, alteration, reconstruction, or change in service that might affect the risk of a discharge or after a discharge/failure due to brittle fracture or other catastrophe, and appropriate action taken as necessary (applies to only field-constructed aboveground containers)	IAM ON OSE	Yes No NA
112.7(j)	Discussion of conformance with applicable more stringent State rules, regulations, and guidelines and other effective discharge prevention and containment procedures listed in 40 CFR part 112	Yes No NA	
112.7(k)	Qualified oil-filled operational equipment is present at the facility 2 Oil-filled operational equipment means equipment that includes an oil storage of present solely to support the function of the apparatus or the device. Oil-filled of storage container, and does not include oil-filled manufacturing equipment (flow operational equipment include, but are not limited to, hydraulic systems, lubrical and other rotating equipment, including pumpjack lubrication systems), gear both systems, transformers, circuit breakers, electrical switches, and other systems device. Check which apply: Secondary Containment provided in accordance with 112.7(containment).	perational equipment is no w-through process). Examating systems (e.g., those oxes, machining coolant sy containing oil solely to end	ot considered a bulk ples of oil-filled for pumps, compressors /stems, heat transfer
112.7(k)	Qualified Oil-Filled Operational Equipment Has a single reportable discharge as described in §112.1(b) from operational equipment exceeding 1,000 U.S. gallons occurred with prior to Plan certification date?	any oil-filled hin the three years	Yes No NA
nent is 601 a	 Have two reportable discharges as described in §112.1(b) from an operational equipment each exceeding 42 U.S. gallons occurred a period within the three years prior to Plan certification date?¹³ 	ny oil-filled within any 12-month	Yes No NA
ALL MEN	If YES for either, secondary containment in accordar	nce with §112.7(c) is re	quired
EM[][]	Facility procedure for inspections or monitoring program to detect equipment failure and/or a discharge is established and documented.	construct all bulk signs	Yes No NA
△E #E	 Does not apply if the facility has submitted a FRP under §112.20: Contingency plan following 40 CFR part 109 (see Appendix C checklist) is provided in Plan AND Written commitment of manpower, equipment, and materials 	☐Yes ☐No ☐NA ☐Yes ☐No ☐NA	Scient

¹¹ Note that a tank car/truck loading/unloading rack must be present for §112.7(h) to apply
12 This provision does not apply to oil-filled manufacturing equipment (flow-through process) testing transfer and transf

ONSHORE FA 40 CFR 112.8	ACILITIES (EXCLUDING PRODUCTION) //112.12	PLAN	FIELD
112.8(b)/ 112.12	2(b) Facility Drainage season of war pour critisk, aske noted medicate blood.	g engled the tracking	nteol
Diked Areas	Drainage from diked storage areas is:	Yes No NA	Yes No NA
(1)	Restrained by valves, except where facility systems are designed to control such discharge, <u>OR</u> Manually activated pumps or ejectors are used and the condition of the accumulation is inspected prior to draining dike to ensure no oil will be discharged	s, or personal salety de rece e ed the con- tidad M s der Killer i se i etz es	rance elemination of the second
(2)	Diked storage area drain valves are manual, open-and-closed design (not flapper-type drain valves)	Yes No NA	Yes No NA
1 411,41	If drainage is released directly to a watercourse and not into an onsite wastewater treatment plant, retained storm water is inspected and discharged per §§112.8(c)(3)(ii), (iii), and (iv) or §§112.12(c)(3)(ii), (iii), and (iv).	Yes No NA	Yes No NA
Undiked Areas (3)	Drainage from undiked areas with a potential for discharge designed to flow into ponds, lagoons, or catchment basins to retain oil or return it to facility. Catchment basin located away from flood areas. 14	☐Yes ☑No ☐NA	Yes No NA
(4)	If facility drainage not engineered as in (b)(3) (i.e., drainage flows into ponds, lagoons, or catchment basins) then the facility is equipped with a diversion system to retain oil in the facility in the event of an uncontrolled discharge. 15	Yes No NA The Use of	1
(5)	Are facility drainage waters continuously treated in more than one treatment unit and pump transfer is needed?	Yes No No NA	☐Yes ☐No ☑NA
If YES	Two "lift" pumps available and at least one permanently installed	Yes No NA	Yes No NA
	 Facility drainage systems engineered to prevent a discharge as described in §112.1(b) in the case of equipment failure or human error 	Yes No NA	Yes No NA
	Burks egiptisted i forestelling diente die feelige vereigietgen van die fin in de Schillebert voor o opt op 100 oordte geen Geente is gebente bit zo omtweet van die geen die fetting bie onteke die terstellige Beglein eigentiel die oorde gewondige ook oberege zijn waard de stooming gebiegie de 100 oktooren betaare begin het bevonte bevereiden begeen die oorde verzie op 200 oktooren 200 oktooren 200 oktooren bis die 200 oktooren begin die bevondig die 100 oktooren die 200 oktooren 20	d dinas in _{englis} din Sun summi quetga en ené districtio mediadi men e disposa faid y	e strupt Present o cardour pont TD
	gridelandific y la	eggggggg tile ordfilli) e	magilion spr
Bulk storage co oil prior to use, bulk storage co	(c) Bulk Storage Containers Intainer means any container used to store oil. These containers are used for pur while being used, or prior to further distribution in commerce. Oil-filled electrical, intainer. containers are not present, mark this section Not Applicable (NA). If present, com-	operating, or manufacturi	ng equipment is not a
(1)	Containers materials and construction are compatible with material stored and conditions of storage such as pressure and temperature	Yes No NA	Yes No NA
(2)	Except for mobile refuelers and other non-transportation-related tank trucks, construct all bulk storage tank installations with secondary containment to hold capacity of largest container and sufficient freeboard for precipitation	☐Yes ☑No ☐NA	
	Diked areas sufficiently impervious to contain discharged oil OR Alternatively, any discharge to a drainage trench system will be safely confined in a facility catchment basin or holding pond	☐Yes ☑No ☐NA ☐Yes ☑No ☐NA	

¹⁴ Do not include oil discharges that result from natural disasters, acts of war, or terrorism in this qualification determination.
¹⁵ These provisions apply only when a facility drainage system is used for containment; otherwise mark NA

	WATER TO LONDON	PLAN	FIELD
(3)	Is there drainage of uncontaminated rainwater from diked areas into a storm drain or open watercourse?	☐Yes ☑No ☐NA	☐Yes ☑No ☐NA
If YES	Bypass valve normally sealed closed	Yes No NA	Yes No NA
	 Retained rainwater is inspected to ensure that its presence will not cause a discharge as described in §112.1(b) 	Yes No NA	Yes No NA
	Bypass valve opened and resealed under responsible supervision	Yes No NA	☐Yes ☐No ☑NA
And head for	Adequate records of drainage are kept; for example, records required under permits issued in accordance with 40 CFR §§122.41(j)(2) and (m)(3)	The No NA	Yes No NA
(4) 26 Pristi 5 NOGLOS	For completely buried metallic tanks installed on or after January 10, 1974 (if not exempt from SPCC regulation because subject to all of the technical requirements of 40 CFR part 280 or 281):	raine a consentivence acidic validante station de acidic littes: Il ligatulia en pamp cutoff	
all ratio grad	Provide corrosion protection with coatings or cathodic protection compatible with local soil conditions		Yes No NA
	Regular leak testing conducted to VID to the trace of the estimate of the result	Yes No NA	☐Yes ☐No ☑NA
(5)	The buried section of partially buried or bunkered metallic tanks protected from corrosion with coatings or cathodic protection compatible with local soil conditions	☐Yes ☐No ☑NA	Yes No NA
4/1 × (6)	Test or inspect each aboveground container for integrity on a regular schedule and whenever you make material repairs. Techniques include, but are not limited to: visual inspection, hydrostatic testing, radiographic testing, ultrasonic testing, acoustic emissions testing, or other system of non-destructive.	Yes No NA E of Delimit to Day Bright Internal His self-of bright the American History of the Self-of t	Yes No NA
Park Josef J.	testing	remains and arranged to the comments of the co	Hoselv I
MI GHI	Appropriate qualifications for personnel performing tests and inspections are identified in the Plan and have been assessed in accordance with industry standards	Yes No NA	✓Yes No NA
	The frequency and type of testing and inspections are documented, are in accordance with industry standards and take into account the container size, configuration and design	Yes No NA	Yes No NA
	Comparison records of aboveground container integrity testing are maintained	Yes No NA	Yes No NA
Asia mala	Container supports and foundations regularly inspected	Yes No NA	✓Yes □No □NA
	Outside of containers frequently inspected for signs of deterioration, discharges, or accumulation of oil inside diked areas	Yes No NA	Yes No NA
A A	Records of all inspections and tests maintained 16 vincence bas to	☑Yes ☐No ☐NA	☑Yes ☐No ☐NA
	Standard identified in the Plan: Valentie of activities in for marky	the state of the s	
API 653		for an extended line upports are properly ne ton and allow for expan	
112.12 (c)(6)(ii)	Conduct formal visual inspection on a regular schedule for bulk	Yes No NA	Yes No NA
(Applies to AFVO Facilities only)	storage containers that meet all of the following conditions: Subject to 21 CFR part 110; Have no external insulation; and Elevated; Shop-fabricated. Constructed of austenitic stainless steel;	viev ziniai somency, , zwiks to glidost at , legs malt canava at si	
	In addition, you must frequently inspect the outside of the container for signs of deterioration, discharges, or accumulation of oil inside diked areas.	□Yes □No ☑NA	☐Yes ☐No ☑NA
	You must determine and document in the Plan the appropriate qualifications for personnel performing tests and inspections. 16	Yes No NA	Yes No NA

¹⁶ Records of inspections and tests kept under usual and customary business practices will suffice

		PLAN	FIELD
(7)	Leakage through defective internal heating coils controlled:	galania/ to ege her. S n drain of page water	safe e
	 Steam returns and exhaust lines from internal heating coils that discharge into an open watercourse are monitored for contamination, <u>OR</u> 	☐Yes ☐No ☑NA	☐Yes ☐No ☑NA
Jord to J	 Steam returns and exhaust lines pass through a settling tank, skimmer, or other separation or retention system 	Yes No NA	☐Yes ☐No ☑NA
(8)	Each container is equipped with at least one of the following for liquid level sensing:	✓Yes ☐No ☐NA	Yes No NA
William I	signal at a constantly attended operation or gauger and p surveillance station, or audible air vent in smaller facilities; Fast response digital compu	e or code signal communic umping station; or e system for determining I ters, telepulse, or direct vi nt to monitor gauges and on an addresses testing)	iquid level (such as sion gauges) and a
(9)	Effluent treatment facilities observed frequently enough to detect possible system upsets that could cause a discharge as described in §112.1(b)	Yes No NA	Yes No NA
(10)	Visible discharges which result in a loss of oil from the container, including but not limited to seams, gaskets, piping, pumps, valves, rivets, and bolts are promptly corrected and oil in diked areas is promptly removed	Yes No NA, the total state of the state of t	☑Yes ☐No ☐NA
(11)	Mobile or portable containers positioned to prevent a discharge as described in §112.1(b).	✓Yes □No □NA	☐Yes ☑ No ☐NA
	Mobile or portable containers (excluding mobile refuelers and other non-transportation-related tank trucks) have secondary containment with sufficient capacity to contain the largest single compartment or container and sufficient freeboard to contain precipitation	☑Yes ☐No ☐NA	☐Yes ☑No ☐NA
112.8(d)/112.12(d)Facility transfer operations, pumping, and facility process	ocemented, are in accordant to any	
(1)	Buried piping installed or replaced on or after August 16, 2002 has protective wrapping or coating	Yes No NA	✓Yes □No □NA
	Buried piping installed or replaced on or after August 16, 2002 is also cathodically protected or otherwise satisfies corrosion protection standards for piping in 40 CFR part 280 or 281	✓Yes No NA	☑Yes ☐No ☐NA
il provide	Buried piping exposed for any reason is inspected for deterioration; corrosion damage is examined; and corrective action is taken	Yes No NA	☑Yes ☐No ☐NA
(2)	Piping terminal connection at the transfer point is marked as to origin and capped or blank-flanged when not in service or in standby service for an extended time	Yes No NA	☑Yes ☐No ☐NA
(3)	Pipe supports are properly designed to minimize abrasion and corrosion and allow for expansion and contraction	☑Yes ☐ No ☐NA	Yes No NA
(4)	Aboveground valves, piping, and appurtenances such as flange joints, expansion joints, valve glands and bodies, catch pans, pipeline supports, locking of valves, and metal surfaces are inspected regularly to assess their general condition	☑Yes ☐No ☐NA	☑ Yes ☐No ☐ NA
l - Dall	Integrity and leak testing conducted on buried piping at time of installation, modification, construction, relocation, or replacement	Yes No NA	Yes No NA
(5)	Vehicles warned so that no vehicle endangers aboveground piping and other oil transfer operations	Yes No NA	Yes No NA
Comments:	and the second of the second second in the second second in the second second in the second second second in the second s	ला व एक शामन सम्बद्ध	rojas 1
thus e.y.			

APPENDIX A: SPCC FIELD INSPECTION AND PLAN REVIEW TABLE

Documentation of Field Observations for Containers and Associated Requirements

Inspectors should use this table to document observations of containers as needed.

Containers and Piping

Check containers for leaks, specifically looking for: drip marks, discoloration of tanks, puddles containing spilled or leaked material, corrosion, cracks, and localized dead vegetation, and standards/specifications of construction.

Check aboveground container foundation for: cracks, discoloration, and puddles containing spilled or leaked material, settling, gaps between container and foundation, and damage caused by vegetation roots.

Check all piping for: droplets of stored material, discoloration, corrosion, bowing of pipe between supports, evidence of stored material seepage from valves or seals, evidence of leaks, and localized dead vegetation. For all aboveground piping, include the general condition of flange joints, valve glands and bodies, drip pans, pipe supports, bleeder and gauge valves, and other such items (Document in comments section of §112.8(d) or 112.12(d).)

Secondary Containment (Active and Passive)

Check secondary containment for: containment system (including walls and floor) ability to contain oil such that oil will not escape the containment system before cleanup occurs, proper sizing, cracks, discoloration, presence of spilled or leaked material (standing liquid), erosion, corrosion, penetrations in the containment system, and valve conditions.

Check dike or berm systems for: level of precipitation in dike/available capacity, operational status of drainage valves (closed), dike or berm impermeability, debris, erosion, impermeability of the earthen floor/walls of diked area, and location/status of pipes, inlets, drainage around and beneath containers, presence of oil discharges within diked areas.

Check drainage systems for: an accumulation of oil that may have resulted from any small discharge, including field drainage systems (such as drainage ditches or road ditches), and oil traps, sumps, or skimmers. Ensure any accumulations of oil have been promptly removed.

Check retention and drainage ponds for: erosion, available capacity, presence of spilled or leaked material, debris, and stressed vegetation.

Check active measures (countermeasures) for: amount indicated in plan is available and appropriate; deployment procedures are realistic; material is located so that they are readily available; efficacy of discharge detection; availability of personnel and training, appropriateness of measures to prevent a discharge as described in §112.1(b).

Container ID/ General Condition ¹⁷ Aboveground or Buried Tank	Storage Capacity and Type of Oil	Type of Containment/ Drainage Control	Overfill Protection and Testing & Inspections
Tanks 01-05, 07, 10	VARIOUS - OOS		
Tank 06	71,400 GAL WASTEWATER		
Tanks 08, 09	1,265,838 GAL EA DIESEL		
Tank 11	6000 GAL? TRANSMIX		
Tank 12	6000 GAL CONTACT WATER		
Tank 13	2000 GAL CONTACT WATER		
CPI SEPARATPR	1500 GAL OILY WATER		
SUMP	200 GAL OILY WATER		
			100
Various drums	55 GAL EA		
<u> </u>			
		=	

¹⁷ Identify each tank with either an A to indicate aboveground or B for completely buried

Provision	Documentation of FIEld Obsen themmoor Containers and Auspolated Requirements
	Tank list does not match the tanks seen at the facility - at least for tanks 11 and 13. In the same to be a seen at the facility - at least for tanks 11 and 13. In the same to be a seen at the facility - at least for tanks 11 and 13.
eliet in bada	Permeability issue has not been satisfactorily corrected.
9-10-10-10-1	Deficiencies for this facility are not being individually addressed, as an enforcement action is being issued at the corporate level.
	wess container and lecentain mand dareng in essed by regulating units.
greneg drie the r a.e.* derra	euk an piping tots oichtets of swaed material, discoloration, codosion, howing of pipe between supports, evidence on technistecpage over lakes or snais, rividance of indiscolorational dead ver, italian for all aircongraund poing wear common tribung forts, value glands and socios, our paras clos supports, bleever star yours valuer, and von pourment is commonly salton of 3112 and or 112,12 (d).
	condary Containment (Active and Passive)
etitivida)	ech desemberg vertismme A form sememment eyntemplantaming wate energiasis by to market of semilier on temperate semianisma äyekem helk is alomine, mulat jämbus "Ciling, sautina, Ernoalombism, promonde of semilier or le huld market mer market til och en semilier i die paramente vestem market enandens
uluseuls stite ts. solets	ech dilice or bean systems for level of precipilation in discercedable sounds absociation slatung of dragons valvas bean imperoscabilly, debas erost or imperoability of the section theories with dragons and knotice of the organ mane around and neighbor containers presence of district gross with milited areas.
	ack drainage systems for: an accumulation of rulthat may have resulted from any small discharge, including lists dr
1112725271741	ary nemneson to construct the construction of
housets L	eck intermon on 1 drawinge painds fort give no available cobactly, presence of spilled in leaved that stall debne at Fortists of
ora zambeo	ack sattys measures (countem-easures) for: amount indicated in plan is available and appropriate, deployment pro
	PHOTO DOCUMENTATION LOG

Photo#	Photographer Name	Instrumentage to Description (include date, location and direction) 1990 101 tentismod location and direction and direct
1	Witul	TANK 1, OUT OF SERVICE; MARKED WITH DATE
2	Witul	TANK 6, CONTACT WATER
3	Witul	TANK 8 NOZZLE W/CORROSION. INSPECTION RECOMMENDATION WAS FOR CLEANING & RECOATING
4	Witul	VIEW OF DIESEL TANK 8
5	Witul	TANK 9, H/S DIESEL
6	Witul	CONTAINMENT AREA WITH SHRUB GROWING. GRATE DOES NOT COVER ANY HOLE/SUMP
7	Witul	DIESEL TANKS WATER DRAW-OFF SUMP/PUMP
8	Witul	FIBERGLAS TANK & TANKS MARKED 13 AND 11. TANK LIST SHOWS 13 AS CONE ROOF, 11 AS HORIZ.
9	Witul	CPI SEPARATOR, PART OF DRAIN SYSTEM FROM TRUCK RACK.
10	Witul	SUPPLY PIPE IN FROM WHARF; ADDITIONAL PIPING NO LONGER USED/CONNECTED.
11	Witul	OUTSIDE OF ORIGINAL CONTAINMENT WALL OF ROCK AND CEMENT.
12	Witul	TRUCK RACK
13	Witul	SIGNAGE WITH INSTRUCTIONS FOR TRUCK LOADING
14	Witul	DISPENSING DRUM IN WAREHOUSE AREA.

APPENDIX B: SPCC INSPECTION AND TESTING CHECKLIST

Required Documentation of Tests and Inspections

Records of inspections and tests required by 40 CFR part 112 signed by the appropriate supervisor or inspector must be kept by all facilities with the SPCC Plan for a period of three years. Records of inspections and tests conducted under usual and customary business practices will suffice. Documentation of the following inspections and tests should be kept with the SPCC Plan.

		Documentation Present Not Present		Not Applicable
	Inspection or Test			
112.7-Gener	al SPCC Requirements	n sentace	ia tremani	10 1 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
(d)	Integrity testing for bulk storage containers with no secondary containment system and for which an impracticability determination has been made		tuliani egra	turally Z
(d)	Integrity and leak testing of valves and piping associated with bulk storage containers with no secondary containment system and for which an impracticability determination has been made	elej e ros spallvou ac	office inst	ua A Ta
(h)(3)	Inspection of lowermost drain and all outlets of tank car or tank truck prior to filling and departure from loading/unloading rack		is in mole	squal (c)
(1)	Evaluation of field-constructed aboveground containers for potential for brittle fracture or other catastrophic failure when the container undergoes a repair, alteration, reconstruction or change in service or has discharged oil or failed due to brittle fracture failure or other catastrophe		ha saldei 230mm nu	est Z
k(2)(i)	Inspection or monitoring of qualified oil-filled operational equipment when the equipment meets the qualification criteria in §112.7(k)(1) and facility chooses to implement the alternative requirements in §112.7(k)(2) that include an inspection or monitoring program to detect oil-filled operational equipment failure and discharges	na villa na	obstance observed	outie
112.8/112.12	Onshore Facilities (excluding oil production facilities)	Leappe	di ke sisa u	entre in
(b)(1), (b)(2)	Inspection of storm water released from diked areas into facility drainage directly to a watercourse, and the storm water released from diked areas into facility drainage directly to	D Suppose	to Institution	- 0-
(c)(3)	Inspection of rainwater released directly from diked containment areas to a storm drain or open watercourse before release, open and release bypass valve under supervision, and records of drainage events		w Lutei	
(c)(4)	Regular leak testing of completely buried metallic storage tanks installed on or after January 10, 1974 and regulated under 40 CFR 112	idos El in	To Ason	e la
(c)(6)	Regular integrity testing of aboveground containers and integrity testing after material repairs, including comparison records	edong site		07177.3
(c)(6), (c)(10)	Regular visual inspections of the outsides of aboveground containers, supports and foundations	to E a s		caty.
(c)(6)	Frequent inspections of diked areas for accumulations of oil	9		
(c)(8)(v)	Regular testing of liquid level sensing devices to ensure proper operation	edo 🗷 a i	ed II dibe	
(c)(9)	Frequent observations of effluent treatment facilities to detect possible system upsets that could cause a discharge as described in §112.1(b)		7 T T 1772	O
(d)(1)	Inspection of buried piping for damage when piping is exposed and additional examination of corrosion damage and corrective action, if present	in tebric et unat <mark>it</mark> in s	7 7	alem II
(d)(4)	Regular inspections of aboveground valves, piping and appurtenances and assessments of the general condition of flange joints, expansion joints, valve glands and bodies, catch pans, pipeline supports, locking of valves, and metal surfaces		og ar historial Vi 💽 i les	Just III
(d)(4)	Integrity and leak testing of buried piping at time of installation, modification, construction, relocation or replacement		E	

APPENDIX C: SPCC CONTINGENCY PLAN REVIEW CHECKLIST

40 CFR Part 109-Criteria for State, Local and Regional Oil Removal Contingency Plans

If a facility makes an impracticability determination for secondary containment in accordance with §112.7(d), it is required to provide an oil spill contingency plan following 40 CFR part 109, unless the facility has submitted a FRP under §112.20. An oil spill contingency plan may also be developed, unless the facility has submitted a FRP under §112.20 as one of the required alternatives to general secondary containment for qualified oil filled operational equipment in accordance with §112.7(k).

109.5–Development and implementation criteria for State, local and regional oil removal contingency plans ¹⁸		Yes	No
(a)	Definition of the authorities, responsibilities and duties of all persons, organizations or agencies which are to be involved in planning or directing oil removal operations.		
(b)	Establishment of notification procedures for the purpose of early detection and timely notification of an oil discharge including:	(3) 19X	
(1)	The identification of critical water use areas to facilitate the reporting of and response to oil discharges.		
(2)	A current list of names, telephone numbers and addresses of the responsible persons (with alternates) and organizations to be notified when an oil discharge is discovered.		
(3)	Provisions for access to a reliable communications system for timely notification of an oil discharge, and the capability of interconnection with the communications systems established under related oil removal contingency plans, particularly State and National plans (e.g., National Contingency Plan (NCP)).		
(4)	An established, prearranged procedure for requesting assistance during a major disaster or when the situation exceeds the response capability of the State, local or regional authority.		
(c)	Provisions to assure that full resource capability is known and can be committed during an oil discharge situation including:		
(1)	The identification and inventory of applicable equipment, materials and supplies which are available locally and regionally.		
(2)	An estimate of the equipment, materials and supplies that would be required to remove the maximum oil discharge to be anticipated.		
(3)	Development of agreements and arrangements in advance of an oil discharge for the acquisition of equipment, materials and supplies to be used in responding to such a discharge.		
(d)	Provisions for well defined and specific actions to be taken after discovery and notification of an oil discharge including:		
(1)	Specification of an oil discharge response operating team consisting of trained, prepared and available operating personnel.		
(2)	Pre-designation of a properly qualified oil discharge response coordinator who is charged with the responsibility and delegated commensurate authority for directing and coordinating response operations and who knows how to request assistance from Federal authorities operating under existing national and regional contingency plans.		
(3)	A preplanned location for an oil discharge response operations center and a reliable communications system for directing the coordinated overall response operations.		
(4)	Provisions for varying degrees of response effort depending on the severity of the oil discharge.		
(5)	Specification of the order of priority in which the various water uses are to be protected where more than one water use may be adversely affected as a result of an oil discharge and where response operations may not be adequate to protect all uses.		
(e)	Specific and well defined procedures to facilitate recovery of damages and enforcement measures as provided for by State and local statutes and ordinances.		

¹⁸ The contingency plan should be consistent with all applicable state and local plans, Area Contingency Plans, and the NCP.